

Projectors

Ricoh PJ WXC4660 and
Ricoh PJ WUC4650

RICOH
imagine. change.

Ultra Short Throw projection for brighter images

Ricoh PJ WXC4660 and PJ WUC4650 are the new Ultra Short Throw projectors with an HLD (High Lumen Density LED) light source technology ensuring 20,000h extremely long life with reduced electricity consumption. Impressive image quality makes these models a perfect fit for mid-sized venues like meeting rooms, board rooms, classrooms and auditoriums. Thanks to the maintenance-free concept (no lamp replacement), the devices could be used for digital signage as well.

- Ultra Short Throw projection from just 75cm for screen size of 130 inches
- Exceptionally long life of 20,000h thanks to the new HLD light source technology
- Powerful speakers and 4,000lm brightness optimal for corporate/ education environments or digital signage
- Flexibility based on compatibility with room control systems like Crestron, AMX and PJ-Link
- Eco-friendly solution with reduced electricity consumption



Hardware specifications

KEY FEATURES	PJ WXC4660	PJ WUC4650
Brightness	4,000 lm	3,600 lm
Throw Ratio	0.27:1 (Ultra Short Throw)	0.27:1 (Ultra Short Throw)
Light Source	High Lumen Density (HLD) LED	High Lumen Density (HLD) LED
Light Source Life	20,000h	20,000h
Resolution	WXGA, 1280x800 pixels	WUXGA, 1920x1200 pixels
Contrast Ratio	500:1	450:1
Device	3-LCD	3-LCD
Screen size	70-130 inches	70-130 inches
Weight	10.9kg	10.9kg
Focus	Manual	Manual
Zoom	Manual	Manual
Zoom Ratio	1.05	1.05
Lens Shift	Horizontal / Vertical (Motorized)	Horizontal / Vertical (Motorized)
Power Consumption	Full: 410W@220V ECO: 288W@220V	Full: 425W@220V ECO: 294W@220V
Standby Power	<0.5V	<0.5V
Noise	Normal 37.5dB, Eco 33.5dB	Normal 37.5dB, Eco 33.5dB
Speaker	2 x 10W	2 x 10W
Network Projection	Wired LAN	Wired LAN
4 Corner Adjustment	Yes	Yes
360° Tilt Free	Yes	Yes
Crestron / AMX / Extron / PJ-Link Compatibility	Yes	Yes
Interface	D-sub-in x1, D-sub-out x1, Video in x1, 3.5mm ST Mini Jack x1(In/out), RCA(R/L)x1, HDMI(MHL) x1, HDMIx1, Control LAN x1, USB Type A x1, USB-B(mini) x1	D-sub-in x1, D-sub-out x1, Video in x1, 3.5mm ST Mini Jack x1(In/out), RCA(R/L)x1, HDMI(MHL) x1, HDMIx1, Control LAN x1, USB Type A x1, USB-B(mini) x1

