

TECHNICAL DATA UTAX DXD 5015

	DISPLAY
Technology	1 x 1.75 cm (0.7") DMD ± 12° Chip DLP™ technology
Resolution (pixel)	1,024 x 768
	IMAGE QUALITY
Brightness	1,500 ANSI lumens
Contrast ratio	2,100 : 1
Projection lamp	156 W P-VIP
Lifetime of lamp (hrs.)	3,000*
	OPTICAL SYSTEM
Lens	F = 2.7 – 2.88, f = 28.33 – 32.73 mm, manual zoom / focus
Projection ratio	2.0 – 2.3 : 1
Image diagonal	0.8 – 6.25 m
Projection distance	1.5 – 10.0 m
	COMPATIBILITY
Horizontal frequency	15 – 80 kHz
Vertical frequency	50 – 85 Hz
Computer resolution	from VGA up to SXGA+
Video	PAL, PAL-N, PAL-M, HDTV (1080i/720p), SECAM
	INPUTS
Computer	1 x Mini D-Sub
Video	1 x component (Mini D-Sub), 1 x S-video, 1 x cinch
Audio	-
Remote	-
	OUTPUTS
Computer	-
Audio	-
	GENERAL
Audio system	-
Main voltage (50 – 60 Hz)	100 – 240 V~
Power consumption max.	200 W, Standby: 9 W
Operation noise	35 dB (A) / 34 dB (A)*
Dimensions (h x w x d)	56 x 200 x 150.5 mm (without feet and lens)
Weight	1.0 kg
Certifications	CE, TÜV, GS
Remote control	automatic picture adjust, control of all functions, source select
Shipping content	projector, soft carrying case, remote control, Mini D-Sub signal cable, S-video and video cable, power cord, lens cap, CD-ROM (user manual)
Optional accessories	spare lamp, cables, projector stands

UTAX DXD 5015 – HIGH PERFORMING BUSINESS TRAVELLER

This compact travel companion offers great performance with 1,500 ANSI lumens. Thanks to modern DLP™ technology this projector delivers brilliant pictures every time. And because of its lightweight design (weighing in at just 1.0 kg) the device goes almost unnoticed.



HIGHLIGHTS

- brightness: 1,500 ANSI lumens
- weight: 1.0 kg
- 2,100 : 1 contrast ratio
- digital vertical keystone correction
- automatic signal identification
- PC control
- electronic fan speed regulation
- eco mode
- OSD in 11 languages
- plug&play

* in eco mode

