



Outstanding Features:

1000 ANSI Lumen delivers a bright, beautiful picture

High Contrast Ratio 3500:1 provides superior black level reproduction

Native 720p High Definition Capability (compatible with 1080i and 720p HD signals)

0.8" DLP™ HD2+ from Texas Instruments

With 1.33 Throw Ratio, it shorten the projection distance (3-meter necessary) to have 100" screen size

2D Lens Shift makes easy installation possible

DLP™ HD2+ HOME CINEMA FRONT PROJECTOR

Product Specifications **CHT726**

Native Resolution	1280 x 720 pixels	
Display Technology	DLP™ HD2+ DMD Chip	
Brightness	1000 ANSI Lumen	
Contrast Ratio	3500:1 (Full on/off)	
Aspect Ratio	16:9 Widescreen Native, 4:3 Compatible	
Color Wheel	6-segment, 5X	
Input Sources	Video	Component* 2
		Video* 1
		S-Video* 1
		VGA* 1
		DVI-D / HDCP* 1
	Control	RS* 232* 1
		IR Receiver* 2
Data Compatibility	VGA, SVGA, XGA	
Video Compatibility	NTSC, PAL, SECAM, SD/ED/HD (720p /1080i Compatible)	
2D Lens Shift	+/- 100% Vertically	
	+/- 15% Horizontally	
Digital Keystoning	+/- 15% Vertical/Horizontal Correction	
Projection Lens	Manual Focus & Zoom, F=2.36~2.5 f=24~30.1	
Zoom Ratio	1.25x: 1	
Throw Ratio	1.33~1.67:1	
Projection Distance	100" at 3-meter	
Image Size (Diagonal)	30"~300"	
Video Enhancement	Motion adaptive de-interlace processor with DCTi/DLTi	
Projection Methods	Front/Rear Desktop, Front/Rear Ceiling	
OSD Control Options	Projector Keypad	
	IR Remote Control	
Lamp	250W (Standard Mode)	
	200W (ECO Mode)	
Audible Noise	30dBA (ECO Mode)	
Dimensions	13.5"*12"* 5.6" (342*306*144mm)	
Weight	14lbs (6.3kg)	
Power Source	90~260V, 50~60Hz	
Power Consumption	360W, Stand-by Mode < 5W	
Operating Temperature	5°C~35°C	
Lamp Warranty	90-Day or 500-Hour	
Product Warranty	Limited 2- Year Parts	