MICROTEK

Digital Projector

MS4

Projection System	
• Native Resolution	800 x 600 (SVGA)
• Max Resolution	1024 x 768 (XGA)
• Display Type	0.55" DDR DLP x 1
• Brightness	1200 ANSI Lumens
• Lamp	200 watt
• Lamp Life	2000 hours
• Brightness Uniformity	80%
• Projection Lens	1: 1.16 manual zoom and focus; F2.44-2.63
• Displayable Colors	24 bit, 16.7million True Color
• Contrast Ratio	1500:1
• Aspect Ratio	4:3 & 16:9
• Projection Distance	4.92' - 23' (1.5m - 7m)
• Screen Size (diagonal)	37" - 202.8" (0.94m - 5.15m)
• Digital Keystone Correction	+/- 15°
• Audio	build-in 1w mono speaker
• Security Lock	Kensington Lock
• Remote Control Features	Wireless remote with laser pointer, mouse function, Power, Auto image, Source select, Keystone, Menu, Enter, Volume (-/+), Arrow Key +/-/up/down, full OSD controls

Technical Specifications	
• Horizontal Scan Rate	15, 31 - 70KHz
• Vertical Refresh Rate	50 - 85Hz
• Installation Options	Front/Rear, Desktop/Ceiling
• Power Consumption	<300 Watts; <20 Watts Standby
• Power Supply Voltage	100 - 240VAC, 50/60Hz
• Operating Temperature	41°F - 95°F (5°C ~ 35°C)
• Dimensions (W x D x H)	280 x 205 x 97mm
• Weight	4.5 lbs (2.04 Kg)
• Audible Noise	35 dB (TYP.)

Connectivity	
• Computer Inputs	DVI-I x1; D-sub HD 15-pin x1; USB x1
• Video Inputs	S-Video x1; Component(thru DVI) x1
• Audio Inputs	mini jack x1
• Video Compatibility	NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM; SDTV: 480i (thru DVI-I); EDTV: 480p, 720p (thru DVI-I); HDTV: 1080i (thru DVI-I)

Included Accessories

Computer Cable, DVI-I to DB15 pin, Audio cable; S-Video cable, AC Power Cable, USB cable, Remote Control with laser pointer & batteries, Quick Setup Guide, User's Manual in multi-language as OSD (CD only), Compac Disc (inf.file), Carrying Case, Lens Cap

MICROTEK

www.microtek.com

Conference Projectors