Philips ProScreen 4100

Brief Introduction Beta 2.5

A brief introduction to the Philips ProScreen 4100. The stationary LCD projector has an SVGA 800 x 600 resolution and a contrast of 150:1. The manufacturer states a lamp life of 4000 hours, which is over 5.5 years with a daily viewing time of 2 hours. A picture width of up to 151 cm is possible. However, the picture should be smaller in room light. We recommend max. 101 cm.

The projector is no longer sold by the manufacturer.

Display Type

1 x 6,4" LCD TFT panel SVGA 4/3 Liquid Crystal Display

Ansi-Lumen Contrast

Black Level

Resolution

Video Modes

Application

300 0 150:1 full on/off 0 2,0000 min. Lumen

ω97 Lux (bei 203 cm Screen)

Lux:97 Lux

4/3 screen width:203 cm

Screen:1 Gain

Room light max.:19 Lux Candela pro m²:31 cd/m²

Foot-Lamberts:9 fL

0.66 min. Lumen

Offset

SVGA 800 x 600

480.000 Pixel

XGA 1024 x 768 compressed

NTSC, PAL, SECAM Pal 60 NTSC 4,43

Stationary | Permanent installation in the training room and meeting room as well as the

conference room.

Very narrow picture width and rooms with very little light.

120W UHP Lamp Light Source Articel Nr.: LCA 3103

Light Life 4000 h.

Operating Costs

Manual Focus

Zoom No Zoom

Objective

Throw Ratio

Audio 6W Mono

> Cinch Video in Stereo Eingang D-sub 15pin in Mini Jack Eingang

S Video Eingang

Yes

Ceiling Mounting

Connections

Power 180W

Size WxHxD

400 x 185 x 330 mm (15,7"x7,3"x13") 24,42 L/dm3 **Operating Noise**

Weight 7,50 kg / 16,53 lbs.

Keystone Vertical Illumination

Frequenz

9 fL / max. 151 cm screen width Foot-Lamberts

31 cd/m²

Remote control with mouse control **Features**

Integrated line doubler

Universal Remote original

In Test

Osram bulb only **NLMP2870**

LCA3103 Lamp original

Fernb-uni-V3 Ceiling Mount 100-120 Halterung100

Order here: https://www.hcinema.de/lampen/shop-en.php?id=n2834 Discontinued (EOL) // Last update of the data: 2023-08-04

Status Data

Optional

More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.