

XGA fixed installation LCD projector



PLC-XF60

- ◆ **6,500 ANSI lumens**
- ◆ **Built-in mechanical shutter system**
- ◆ **1300:1 contrast ratio**
- ◆ **Detachable terminals for system up**
- ◆ **Superior HDTV Image Performance with New Progressive System (2-3/2-2 Pull Down)**
- ◆ **Full 10 bit video circuit**

Model Name	SANYO PLC-XF60
Panel	1.4inch TFT p-Si x 3 with micro lens
Number of pixels	2,359,296 (1024x768 dots)
Projection lamp	UHP300W x 2
Brightness	6500 ANSI lm, Contrast 1300:1
Uniformity	90%(corner to center)
Optional Lens	LNS-W01Z/W02Z/W03/W04/S01/S02Z/S03/M01Z/T01Z/T02/TO3
Signal Terminals	Input 1: DVI-D / RGB (D-Sub 15), Sterio (mini jack) Output RGB (D-Sub 15) Monitor Out Input 2: RGBHV/ Y,Pb/Cb,Pr,Cr, Stereo (mini jack) Input 3: Composite (RCA) / S-Video (mini DIN4) / Y,Pb/Cb,Pr/Cr (RCA x 3), Stereo (RCA x 2) Input 4: DVI-D (Warp & Blending Board) Input 5: Detachable Terminals for system up
Option Terminal	DVI (HDCP) / Dual SDI / Faroudja Video / Network RGB (D-Sub 15) / 5BNC (RGBHV only)
Communication Terminal	RS232C In / Out (D-Sub 9x2), USB (A/B – type)
Other Terminal	Wired remote control (mini jack)
Colour systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
Computer compatibility	UXGA/SXGA/XGA/SVGA/VGA/MAC
Exclusive Terminal	For smoke resistant box (optional)
Other Features	Keystone Correction / Lens Shift (U/D/R/L), Lens Memory / Security Locks / Control Pad
Scanning frequency	H/V sync -120kHz, - 120Hz Dot clock 230 MHz
Sound output	3.0W Stereo
Fan Noise	42 dB (Normal) / 39 dB (Eco)
Voltage	100V-240V AC (auto voltage)
Dimensions (W x H x D)	518 x 252 x 606 mm
Weight	24.7 kg