Sony VPL V800Q



Display Type

3 x 1,3" LCD TFT Panel VGA 4/3 Liquid Crystal Display

*Projector Ansi-Lumen 800 Contrast

Black Level Offset

VGA 640 x 480 Resolution

307.200 Pixel Video Modes NTSC, PAL-M, PAL-N, SECAM

Stationary | Permanent installation in the training room and meeting room as well as the conference

တ္ 259 Lux (bei 203 cm Screen) ဝှင် ---

Application

Small screen width, rooms with very little ambient light below 100 lumens.

Light Source Light Life

400W Metalldampf Lamp

Operating Costs -

Focus Powered

Zoom Powered 1,6

Objective F=2,5-3,1 f=50-80 mm

Throw Ratio 1,89-3,03:1

Audio

5 x BNC RGBHV in BNC Video in und out

1x S-Video Connections 1x Video (Cinch),

> Mini Jack RS422A in

Ceiling Mounting -

Power 570W / 15W standby

480 x 239 x 663 mm (18,9"x9,4"x26,1") 76,06 L/dm3 Size WxHxD

Operating Noise -

25,00 kg / 55,12 lbs.

Illumination

H-sync: 15-65 kHz V-sync: 38-120 Hz

Foot-Lamberts 24 fL / max. 246 cm screen width

82 cd/m²


Features

- Discontinued (EOL) // Last update of the data: 2023-08-04

Data



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.



Screen:1 Gain

Weight Keystone

Frequenz

Status

More Details