enlighten your audience



Firefly™ P1000 XGA Video Projector



Bright and light.


Put the two features in a high performance XGA data/video projector, and as a mobile presenter you're good to go. That's exactly what Telex has done with the portable new Firefly™ P1000 Notebook Video Projector. With 1000 ANSI lumens of projection power and a weight of under ten pounds (4.5 kg), the P1000 has what it takes for you to hit the ground running. Compatible with resolution formats up to 1600 x 1200 and capable of showing the latest in high definition video, the true XGA (1024 x 768) P1000 projects the rich, saturated images and fine detail that you'd expect from a boardroom style projector. The Firefly P1000 includes wireless mouse, laser pointer and digital "picture in picture" zoom control in the remote so it's easy to conduct your presentations with total confidence.

See reverse side for complete specifications, or for more information, contact:
Telex Communications, Inc., 9600 Aldrich Ave. So., Minneapolis, MN 55420; (800) 828-6107, ext. 443, (612) 887-7443.
You can also reach us on the Internet at www.telex.com. Our e-mail address is: multimedia@telex.com.



TELEX®

Firefly™ P1000 XGA Video Projector



S P E C I F I C A T I O N S



LCD Type:	0.9″ x 3 active matrix TFT high aperture
Brightness:	1000 ANSI lumens (typical)
Contrast:	Greater than 200:1
Scan Rate:	15 - 106 kHz horizontal, 50 - 85 Hz vertical
Resolution:	XGA (1024 x 768) native, 640 x 400 to 1600 x 1200 in scaled or condensed mode
Aspect ratio:	4:3 standard, 16:9 in HDTV and in anamorphic DVD and laserdisc video
Lens:	F1.8-2.1 (1.3:1) manual zoom/focus
Weight:	9.9 lbs (4.5 kg)
Size:	10.4″ W x 4.5″ H x 13.4″ D (264x115x340mm)
Power:	100-240 vac 50/60 Hz (worldwide ready)
Inputs:	Audio (1) RCA RGB (1) 15-pin HD-Sub (computer, component and HDTV video) Video (1) RCA S-Video (1) 4-pin DIN
Outputs:	Audio (1) 3.5mm mini jack RGB (1) 15-pin HD-Sub
Remote:	Full control, with PC card control, mouse control, laser pointer
Speakers:	(1) 1 watt mono
Accessories:	(Included) remote, CD-ROM software, lens cap, RGB cable, power cord, RS232 cable, MAC adapter, PS/2 adapter

SCREEN SIZE						DISTANCE			
Diagonal Size		Height Size		Width Size		MAX. Zoom		MIN. Zoom	
INCH	CM	INCH	CM	INCH	CM	INCH	CM	INCH	CM
23	58	13.8	35	18.4	46	–	–	44.1	112
40	102	24	61	32	81	61	155	79.1	210
60	152	36	91	48	122	92.9	236	120	305
80	203	48	122	64	162	125	317	161	409
100	254	60	152	80	203	157	398	202	513
150	381	90	228	120	305	237	602	305	774
200	508	120	305	160	406	317	805	407	1033
245	622	147	373	196	498	389	988	–	–

PCMCIA card slot for "computer free" presentations with PC Card Viewer software included

Auto-play your presentations from 3-99 seconds per slide or photo

Digital keystone correction

25X digital zoom feature includes "Picture in Picture"

Color temperature control (gamma correction)-user definable

RS-232 control with ASCII commands available

Auto-sync on demand

Accepts HDTV (RGBHV) Video (displayed in 16:9)

Project from the front, the rear or the ceiling

High performance optical zoom from 23" to 245"

Automatic shut down feature

2000 hour NSH lamp



At just 9.9 lbs and with 1000 ANSI lumens, the P1000 is truly light and bright.

TELEX®

TELEX COMMUNICATIONS, INC.

9600 Aldrich Ave. So., Minneapolis, MN 55420 U.S.A.
Telephone: (800) 828-6107, ext 443, (612)887-7443
Fax: 612-884-0043
E-mail: multimedia@telex.com
Web: www.telex.com

U.K. Office
Tel: +44 (0) 1908 690880
Fax: + 44 (0) 1908 694020

Australia Office
Tel: +61 29 648 3455
Fax: +61 29 648 5585

Canada Office
Tel: 416-431-4975
Fax: 416-431-4588

Germany Office
Tel: +49 9421 706 392
Fax: +49 9421 706 287

Hong Kong Office
Tel: +852 2 351 3628
Fax: +852 2 351 3329

Singapore Office
Tel: +65 746 8760
Fax: +65 746 1206

Form No. MB 20585 Specifications subject to change without notice Litho USA 5/99 ZM