

Vivibright GP8S



VIVIBRIGHT GP8S



Brief Introduction

Beta 2.5

The GP8S LCD has 100 Ansi lumens, a contrast of 300:1 and a HVAG 480 x 320 resolution. An image width of up to 87 cm is possible. However, the image should be smaller in room light. We recommend max. 58 cm. The projector was launched in 2014 and is no longer sold by the manufacturer.

Display Type

1 x LCD TFT Panel
HVAG 4/3 Liquid Crystal Display

Ansi-Lumen

100

33 Lux (bei 200 cm Screen)

Contrast

300:1 full on/off

300:1 full on/off

Black Level

0,3333 min. Lumen

0,111 min. Lumen

Offset

-

Resolution

HVAG 480 x 320
153.600 Pixel

Video Modes

Pal, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Application

Game-Portabel | Very portable, small-screen projections.

Light Source

LED

Light Life

-

Operating Costs

0,00 € LED

Focus

Manual

Zoom

No Zoom

Objective

-

Throw Ratio

1,16:1

Audio

2 x 2W

Connections

HDMI in
D-sub 15pin in und out
Cinch Video in
USB in
SD-Card slot

Ceiling Mounting

Nein

Power

32W

Size WxHxD

127 x 56 x 126 mm (5"x2,2"x5") 0,9 L/dm³

Operating Noise

31dB



Weight

0,500 kg / 1,1 lbs.

Keystone

-

Illumination

-

Frequenz

-

Foot-Lamberts

3 fL / max. 87 cm screen width
10 cd/m²

Features

■ SD-Card slot

Status

2014 Discontinued (EOL) // Last update of the data: 2023-08-04

Data



HCinema

<https://www.projector-database.com/pro/vivibrightgp8s-en.html>

More Details

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.